

Barbed wire



Description

Barbed wire is a kind of modern security fencing materials fabricated with high-tensile wire. It has single twist and double twist two type. Barbed Wire can be installed to achieve the result of frightening and stopping to the aggressive perimeter intruders, with piecing and cutting razor blades mounted at the top of the wall, also the special designs making climbing and touching extremely difficult. The wire and strip are galvanized to prevent corrosion.

Currently, Barbed Wire been widely used by many countries in military field, prisons, detention houses, government buildings and other national security facilities. Recently years, barbed tape has apparently become the most popular high-class fencing wire for not only military and national security applications, but also for cottage and society fence, and other private buildings.

New Technology: Electrophoretic paint barbed wire

Our engineers team have researched new technology of electrophoretic paint in wire mesh products in recently years. Firstly application in barbed wire industry base on the traditional hot dipped galvanized. And got the patent (No.ZL201220274868.7), Solved the distraught problem of rust on cutting section. This technology have landmark signification in security fence industry.

Barbed Wire Features

- ❖ Various surface treatment can be chose, galvanized, powder coating, pvc coated, Electrophoretic paint
- ❖ Sharp barb
- ❖ Quick and easy for installation

Barbed Wire Application

It is used as security fencing and isolation for gardens, residences, military sites, border protection, prison, and anywhere sites requiring high security.

Single twist barbed wire specification

Wire(mm)	Barbs Spacing(mm)
1.8×1.8	50-150
2.0×2.0	50-150

Company: Anping County Hangtong Wire Mesh Co., Ltd.

Address: East of Baoheng Road, South of Anping County, Hebei P.R China.

Website: <http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613



Anping County Hangtong Wire Mesh Co.,LTD

Best fence for global market.

2.2×2.0	50-150
2.5×2.2	50-150
2.6×2.2	50-150
2.7×2.2	50-150
2.8×2.2	50-150
3.0×2.2	50-150

Specification

Double twist barbed wire specification	
Wire(mm)	Barbs Spacing(mm)
1.4×1.4	101.6-127
1.5×1.5	101.6-127
1.6×1.6	101.6-127
1.7×1.7	101.6-127
1.8×1.8	101.6-127
1.9×1.9	101.6-127
2.0×2.0	101.6-127

Material

Wire and barb used high quality low carbon steel wire,galvanized or pvc coated wire.

Surface:Galvanised, Pvc coated,Electrophoretic paint.

Above all material from famous factory.

Powder from AKZONOBEL,Paint from Nippon.

Trade Item

Delivery Terms:FOB, CIF

Payment Currency:USD, EUR, AUD,JPY, CAD, GBP, CNY

Payment Item:T/T, L/C, PayPal, Escrow

Nearest Port:Xingang port,Qingdao port

Delivery Time:General after 25days upon received T/T30% advance payment

Popular Payment detail: T/T 30% in advance as deposit, the balance against received the copy of B/L.

Company:Anping County Hangtong Wire Mesh Co.,Ltd.

Address:East of Baoheng Road,South of Anping County,Hebei P.R China.

Website:<http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613