

Serried vertical wire fence



Description

Serried vertical wire fence is composed with quadrate post or circular post and high strength welded wire fence; Welded wire fence using high quality steel wire to welded . Dia 3.0----4.0mm, Mesh size designed as 12.7(Vertical wire to wire to or center to center)*76.2mm(horizontal wire to wire or center to center); Welded point have high tensile strength. And better planeness . Surface have a strong erosion resistance and anti-ultraviolet ; Connect by screw flat bar , the installation is very easy and convenience

Serried vertical wire fence features

- ❖ Width from 2100----2600 all available .
- ❖ Serried vertical wire fence ,have good ability to anti --climb and anti-cut.
- ❖ Wire diameter:from3.0 -----to 4.0mm
- ❖ Hot dipped galvanized after fabricated
- ❖ Hot dipped galvanized after fabricated and then powder sprayed coating.
- ❖ Hot dipped galvanized wire welded and then powder sprayed coating.
- ❖ Extra choose the barbed wire or razor wire fence make more security .

Serried vertical wire fence application

It is often used in Power station, Commonality construction,Jail, Airport, Military base,Country border and other high security area and place.

Specifications

Fence height(mm)	Fence width(mm)	Wire Diameter (mm)	Mesh size (mm)	Square Post Section(mm)	Circular Post(mm)	Post Height (mm)
1220	2500	3.0	76.2×12.7	60×60 ×2.0	60×2.0	1600

Company:Anping County Hangtong Wire Mesh Co.,Ltd.

Address:East of Baoheng Road,South of Anping County,Hebei P.R China.

Website:<http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613



Anping County Hangtong Wire Mesh Co.,LTD

Best fence for global market.

1500	2500	3.0	76.2×12.7	60×60 ×2.0	60×2.0	1900
1800	2500	3.0	76.2×12.7	75×75 ×2.0	75×2.0	2200
2100	2500	4.0	76.2×12.7	80×80 ×2.0	89×2.0	2600
2400	2200	4.0	76.2×12.7	80×80 ×2.0	89×3.0	3000
3000	2200	4.0	76.2×12.7	100×100×3.0	89×3.0	3600

Material

Mesh panel using high quality low carbon steel wire and welded by computer controlled machine. Post using international standard tube as material (60×60×2.0mm,75×75×3.0mm,80×80×3.0mm,100×100×3.0mm or Dia 60×2.0,89×3.0mm)

Fixings: steel brackets or flat bar, Self-break bolts adopting Stainless or Hot dipped galvanized.

Surface: Fence can use pre hot dipped galvanized wire or tube fabricate and after several clear procedure. We use famous international powder (AkzoNobel)sprayed.In that case can got strongly resist the corrosive and ultraviolet radiation. Double coating layer high quality anti corrupt . The longevity will 10 years long.

Hot dipped galvanized after fabricated ,The Zn can got 500---60g/m2. Longevity will got more than 15 years.

Trade Item

Delivery Terms:EXW , FCA,FAS,FOB,CFR, CIF,CPT,CIP

Payment Currency:USD, EUR, AUD,JPY, CAD, GBP, CNY

Payment Item:T/T, L/C, PayPal, Escrow

Nearest Port:Xingang port,Qingdao port

Delivery Time:General after 25days upon received T/T30% advance payment

Popular Payment : T/T 30% in advance deposit, the balance against received the copy of B/L.

Company:Anping County Hangtong Wire Mesh Co.,Ltd.

Address:East of Baoheng Road,South of Anping County,Hebei P.R China.

Website:<http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613