

Bent top palisade fence



Descrition

Bent top Palisade fencing offers the best there is in a hig security fence, a durable versatile fence at a cost effective price.Simple to install, the individual components are hot dip galvanised prior to leaving our factory and no further welding, cutting or drilling is necessary, ensuring total corrosion protection and minimising installation time and costs.

Palisade is more secure than other fencing systems, so wherever security is a priority, Palisade is used.Steel palisade fencing is especially popular for schools, park and industrial sites because of its high damage resistance and the fact that it is so difficult to climb.

As palisade fencing manufacturer,HT-Fence supply both the W section and the D section style of palisade fencing, with the integrity of the palisade fence being maintained by the two horizontal rails that are used as standard in palisade fences up to three metres high. However, we can supply other heights of palisade fencing as your required.

Bent Top Palisade Fence Features

- Bolt-on Palisade fencing can be installed by semi-skilled staff as there is no welding on site.
- Bolt-on Palisade fencing is easily transported. The components are packed in bundles.
- Bolt-on Palisade fencing which has been hot-dip galvanized is not compromised by welding on site.
- Bolt-on Palisade fencing can be easily moved to another fence line.
- Bent top can provide highest level security protection
- HT-Fence Palisade fencing is modular. Sections can be replaced easily if damaged by vehicles, falling trees, etc.

Palisade Fence Application

It is often used in villa, park, industrial plants, garden, is ulated of road, school, station, residence community, etc.



Specifications

Bent Top Pale head:Can be do single pointed, triple pointed, square tops, round and notched tops or rounded only.

Panel size		W Pale section:62&70mm		Rails	Post	
Fence heights	Post Distance	Pale Thickness	Qty:Pale	Cross Rails	Height	I Post Section
1.8m	2.75 m	1.5/2/2.5/3mm	17pcs	$40 \times 40 \times 4mm$	2400	100×55mm
				$50 \times 50 \times 5$ mm		
				$50 \times 50 \times 6$ mm		
2.1m	2.75m	1.5/2/2.5/3mm	17pcs	$40 \times 40 \times 4mm$	2900	100×55mm
				$50 \times 50 \times 5mm$		
				$50 \times 50 \times 6$ mm		
2.4m	2.75m	1.5/2/2.5/3mm	17pcs	$40 \times 40 \times 4$ mm	3200	100×55mm
				$50 \times 50 \times 5$ mm		
				$50 \times 50 \times 6$ mm		
3.0m	2.75m	1.5/2/2.5/3/3.5m	17pcs	$40 \times 40 \times 4$ mm	3900	100×55mm
		m		$50 \times 50 \times 5$ mm		
				$50 \times 50 \times 6$ mm		
D Pale section:65mm						
1.8m	2.75m	1.5/2/2.5mm	17pcs	$40 \times 40 \times 4mm$	2400	100×55mm
				$or50 \times 50 \times 5mm$		
2.1m	2.75m	1.5/2/2.5mm	17pcs	$40 \times 40 \times 4mm$	2900	100×55mm
				or50×50×5mm		
2.4m	2.75m	1.5/2/2.5mm	17pcs	40×40×4mm	3200	100×55mm
				or50 $ imes$ 50 $ imes$ 5mm		
3.0m	2.75m	1.5/2 <mark>/2</mark> .5mm	17pcs	$40 \times 40 \times 4$ mm	3900	100×55mm
				or50 $ imes$ 50 $ imes$ 5mm		

Materail

Pale use mild steel plate(black or galvanised) Horizontal rails:Standard $50 \times 50 \times 6$ mm angle rail Post use I beam(100×55 mm, 100×68 mm, 126×76 mm) Fixings:Steel plate: $40 \times 8 \times 150$ mm Bolts:M 8×30 ,M 12×30 anti-vandal steel or stainless steel Surface:Galvanised or galvanised then powder coating fininshed Steel grade can be chose. Powder from AKZONOBEL

Trade Item

Delivery Terms: FOB, CIF

Company:Anping County Hangtong Wire Mesh Co.,Ltd. Address:East of Baoheng Road,South of Anping County,Hebei P.R China. Website:http://www.hangtongfence.com Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613



Anping County Hangtong Wire Mesh Co.,LTD Best fence for global market.

Best fence for global mar

Payment Currency:USD, EUR, AUD, JPY, CAD, GBP, CNY Payment Item:T/T, L/C, PayPal, Escrow

rayment item. 171, L/C, rayral, Esciow

Nearest Port:Xingang port,Qingdao port

Delivery Time:General after 25days upon received T/T30% advance payment

Popular Payment detail: T/T 30% in advance as deposit, the balance against received the copy of B/L.

IT-FENCE