

Pressed spear fence/Picket fence



Description

Adopted high quality hot dipped galvanized steel tube. Top vertical tube pressed to spear by heavy duty punch . Horizontal rail is punched holes which can insert vertical rail. Combine strongly by our exquisite clamp. Other way is vertical welded to horizontal bar directly . Spear fence /Picket fence' s artistic and practice are complimentary by client.

Pressed spear fence / Picket fence features

- ❖ Available as any high , the fencing can be supplied as client requirements.
- ❖ Width from 2100----2600 all available .
- ❖ Rail can making 2 pcs /panel,3pcs/panel ,4pcs/panel.
- ❖ Decorative accessories on rails available.
- ❖ Pale welded face on rail,or punched through rail and welded,or using specialized clamp to connected.

Pressed spear fence / Picket fence features application

It is often used in Villa, Garden, Residence community , industry area and so on.

Specifications

Pale head:pressed spear fence

Pale welded face on rail.

Panel size		Pale: 19×19,25×25		Rails	Post	
Fence height(mm)	Fence width(mm)	Pale Thickness(mm)	Qty:Pale (pcs)	Cross Rails (mm)	Height (mm)	Square Post Section(mm)
1800	2400	1.2/1.6	18	40×40×1.6/2.5	2700	65×65 ×3.0
2100	2400	1.2/1.6	18	40×40×1.6/2.5	3000	65×65 ×3.0
2400	2400	1.2/1.6	18	40×40×1.6/2.5	3300	65×65 ×3.0
2700	2100	1.2/1.6	15	40×40×1.6/2.5	3600	75×75 ×3.0
3000	2750	1.2/1.6	17	40×40×1.6/2.5	3900	75×75 ×3.0

Company:Anping County Hangtong Wire Mesh Co.,Ltd.

Address:East of Baoheng Road,South of Anping County,Hebei P.R China.

Website:<http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613



Anping County Hangtong Wire Mesh Co.,LTD

Best fence for global market.

Pale punched through rail

Panel size		Pale:19×19,25×25		Rails	Post
Fence height(mm)	Fence width(mm)	Pale Thickness(mm)	Qty:Pale(p cs)	Cross Rails (mm)	Height (mm) Square Post Section(mm)
1800	2400	1.2	18	40×40×1.2/1.6	2700 65×65 ×2.0
2100	2400	1.2	18	40×40×1.2/1.6	3000 65×65 ×2.0
2400	2400	1.2	18	40×40×1.2/1.6	3300 65×65 ×2.0
2700	2100	1.2	15	40×40×1.2/1.6	3600 65×65 ×2.0

Material

Pale use galvanized mild steel tube

Horizontal rails:Standard 40×40×1.6/2.5 or40×40×1.2/1.6 mm steel tube

Post use (60×60×2.0mm ,65×65×2.0mm, 75×75×3.0mm,80×80×3.0mm)

Fixings: steel brackets or aluminum brackets.

Bolts and Nuts:Stainless steel304.

Surface: Fence can use pre hot dipped galvanized tube fabricate and after several clear procedure. We use famous international powder (AkzoNobel)sprayed.In that case can got strongly resist the corrosive and ultraviolet radiation. Double coating layer high quality anti corrupt . The longevity will 10 years long.

Trade Item

Delivery Terms:EXW , FCA,FAS,FOB,CFR, CIF,CPT,CIP

Payment Currency:USD, EUR, AUD,JPY, CAD, GBP, CNY

Payment Item:T/T, L/C, PayPal, Escrow

Nearest Port:Xingang port,Qingdao port

Delivery Time:General after 25days upon received T/T30% advance payment

Popular Payment : T/T 30% in advance deposit, the balance against received the copy of B/L.

Company:Anping County Hangtong Wire Mesh Co.,Ltd.

Address:East of Baoheng Road,South of Anping County,Hebei P.R China.

Website:<http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613