

Garrison fence



Description

The test of time puts replacement fencing on capital expense list again and again . Time consuming, cost consuming and often interruptive to the premises security .Solution--- Garrison fence.

This heavy duty tubular fence makes intrusion extremely difficult. Finished with an aggressive pointed top, The fence is dangerous to climb. In the event there often ends in arrest for the intruder .

Garrison fence features

- ❖ Available as standard 2100mm high , the fencing can be supplied as 1800mm or 2400mm, and made to measure between pillars on front alignments.
- ❖ Gates are also matching and using heavy duty hinges, provide years of trouble free service. Lasting for longer than wire fencing solves the ongoing capital expenses of wire fence maintenance and replacement . Powder coated to suit your landscape and building.
- ❖ There are two kinds of type: welded face on rail, or punched through rail.

Garrison fence Application

This fence is the premium boundary solution for industrial and commercial properties.

Specifications

Pale head: aggressive pointed top

Pale welded face on rail.

Panel size		Pale: 25 × 25		Rails		Post
Fence height(mm)	Fence width(mm)	Pale Thickness(mm)	Qty:Pale(pcs)	Cross Rails (mm)	Height (mm)	Square Post Section(mm)
1800	2400	1.6	18	40 × 40 × 2.5	2700	65 × 65 × 3.0
2100	2400	1.6	18	40 × 40 × 2.5	3000	65 × 65 × 3.0
2400	2400	1.6	18	40 × 40 × 2.5	3300	65 × 65 × 3.0
2700	2100	1.6	15	40 × 40 × 2.5	3600	75 × 75 × 3.0
3.0m	2750	1.6	17	40 × 40 × 2.5	3900	75 × 75 × 3.0

Company:Anping County Hangtong Wire Mesh Co.,Ltd.

Address:East of Baoheng Road,South of Anping County,Hebei P.R China.

Website:<http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613



Anping County Hangtong Wire Mesh Co.,LTD

Best fence for global market.

Pale punched through rail

Panel size		Pale: 25×25		Rails	Post
Fence height(mm)	Fence width(mm)	Pale Thickness(mm)	Qty:Pale(p cs)	Cross Rails (mm)	Height(mm) Square Post Section(mm)
1800	2400	1.2	18	40×40×1.6	2700 65×65×2.0
2100	2400	1.2	18	40×40×1.6	3000 65×65×2.0
2400	2400	1.2	18	40×40×1.6	3300 65×65×2.0
2700	2100	1.2	15	40×40×1.6	3600 65×65×2.0

Material

Pale use galvanized mild steel tube

Horizontal rails: Standard 40×40×2.5 or 40×40×1.6 mm steel tube

Post use (65*65*3.0mm ,65*65*2.0mm, 75*75*3.0mm)

Fixings: steel brackets or aluminum brackets.

Surface:Galvanized or galvanized then powder coating finished. Standard ral colour for client choose.

Steel grade can be chose.

Trade Item

Delivery Terms:EXW , FCA,FAS,FOB,CFR, CIF,CPT,CIP

Payment Currency:USD, EUR, AUD,JPY, CAD, GBP, CNY

Payment Item:T/T, L/C, PayPal, Escrow

Nearest Port: Xingang port,Qingdao port

Delivery Time:General after 25days upon received T/T30% advance payment

Popular Payment : T/T 30% in advance deposit, the balance against received the copy of B/L.

Company:Anping County Hangtong Wire Mesh Co.,Ltd.

Address:East of Baoheng Road,South of Anping County,Hebei P.R China.

Website:<http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613