Anping County Hangtong Wire Mesh Co.,LTD Best fence for global market.

Single gate



Description

Single gate perfectly combine with around fencing, showing excellent integrality.

Opening as 180 degree, for coming and going is very smoothly.

Gate post making as quadrate post or circular tube, attached heavy duty hinge, Stainless safety lock system. And high strength welded wire panel composed with frame; Dia 3.0----8.0mm, Mesh size designed as 50*50mm,50*100mm,50*200mm; Also the panel can design double wire weded 6/6/6mm, 8/6/8mm. Vertical tube welded on the frame for gate is available. After high quality powder coating, there have a strong erosion resistance and anti-ultraviolet; The installation is very easy and convenience

Single gate features

- ❖ Width from 800----1500mm all available .
- Height from 1500-----2100mm,
- Wire diameter of panel which welded on frame:from 3.0 -----to 8.0mm
- Pre galvanized wire welded panel, Pre galvanized tube welded frame.
- Powder sprayed coating after fabricated.
- Any Ral colour available for client choose.

Single gate application

It is very popular used in Garden, Villa, School , Commercial premises and sports area.

Specifications

Gate height(mm)	Fence width(m m)	Wire Diameter (mm)	Mesh size (mm)	Square Post Section(mm)	Circular Post(mm)	Post Height (mm)
1000	800	4.0	50×50	60×60 ×2.0	60×2.0	1400
1200	800	4.0	50×50	60×60 ×2.0	60×2.0	1600
1500	800	4.0	50×50	60×60 ×2.0	60×2.0	1900



Anping County Hangtong Wire Mesh Co.,LTD Best fence for global market.

Best lence for global market.										
1800	900	5.0	50×200	75×75 ×2.0	75×2.0	2200				
2000	1000	5.0	50×100	80×80 ×2.0	80×2.0	2600				
2100	1500	5.0	50×200	100×100 ×2.0	100×3.0	2700				
Gate height(mm)	Fence width(m m)	Vertical tube (mm)	Tube distance (mm)	Square Post Section(mm)	Circular Post(mm)	Post Height (mm)				
1000	800	20×20×1.5	125×125	60×60 ×2.0	60×2.0	1400				
1200	800	20×20×1.5	125×125	60×60 ×2.0	60×2.0	1600				
1500	800	25×25×1.5	125×125	60×60 ×2.0	60×2.0	1900				
1800	900	25×25×1.5	125×125	75×75 ×2.0	75×2.0	2200				
2000	1000	25×25×1.5	125×125	80×80 ×2.0	80×2.0	2600				
2100	1500	25×25×1.5	125×125	100×100 ×2.0	100×3.0	2700				

Material

Mesh panel using high quality low carbon steel wire and welded by computer controlled machine. Post using international standard tube as material ($60 \times 60 \times 2.0$ mm , $75 \times 75 \times 3.0$ mm, $80 \times 80 \times 3.0$ mm, 100×3.0 mm or Dia 60×2.0 mm, 75×2.0 mm, 80×2.0 mm, 89×3.0 mm , 100×3.0 mm), Frame adopted Pre galvanized tube welded($30 \times 30 \times 1.0$ mm)

5mm, $40\times40\times1.5$ mm, $40\times60\times1.5$, $60\times60\times1.5$ mm)

Fixings: Heavy duty hinges, Stainless Steel lock system.

Surface: Gate use pre hot dipped galvanized wire or tube fabricate and after several clear procedure. We use famous international powder (AkzoNobel) sprayed.In that case can got strongly resist the corrosive and ultraviolet radiation. Double coating layer high quality anti corrupt. The longevity will 10 years long.

Hot dipped galvanized after fabricated ,The Zn can got 500----60g/m2. Longevity will got more than 15 years.

Trade Item

Delivery Terms: EXW , FCA, FAS, FOB, CFR, CIF, CPT, CIP

Payment Currency: USD, EUR, AUD, JPY, CAD, GBP, CNY

Payment Item:T/T, L/C, PayPal, Escrow

Nearest Port:Xingang port,Qingdao port

Delivery Time:General after 25days upon received T/T30% advance payment

Popular Payment: T/T 30% in advance deposit, the balance against received the copy of B/L.