

Welded Wire Panel Fence/3D Fence Panel



Description

3D fence panel is a type of welded wire mesh which has V-shaped strengthen bending curves. It is made of high quality low carbon steel wire, galvanized wire. Then will be hot dipped galvanized, powder coated or pvc coated. It looks modern and attractive. Mainly used for security protection in construction site, residential building, sports field, warehouse, highway or airport service area, railway station, etc.

The height are available in a range of heights from 630 till 2430 mm.

The panels have vertical barbs of 30 mm that can be placed at the top or at the bottom.

The horizontal reinforcements of Bekafor Classic give the panels extra rigidity.

The popular wire diameter are 4.0mm and 5.0mm, mesh holes are $50 \times 100\text{mm}$, $50 \times 150\text{mm}$, $50 \times 200\text{mm}$, others are available.

Posts are manufactured from steel tubular section with threaded inserts for fixing the steel mesh clips. Additional fixings are provided to accommodate stepping of panels where the fence is installed on a gradient.

The general post section are $60 \times 60\text{mm}$, $60 \times 80\text{mm}$, $75 \times 75\text{mm}$, others are available.

HT-Fence welded wire panel fence is manufactured from galvanised material, powder coated and pvc coated. The popular color is Green RAL 6005 .If others color is required, we're easily able to provide this. All of our fence power from AKZONOBEL Company.

Welded wire panel fence/3D Fence Panel Features

- ❖ Attractive and cost effective solution.
- ❖ Panels have a high level of rigidity
- ❖ Quick and Easy install
- ❖ Various color choice.

Welded wire panel fence/3D Fence Panel Application

It is often used in villa, park, industrial plants, garden, isolated of road, school, station, residence community, etc.

Company: Anping County Hangtong Wire Mesh Co., Ltd.

Address: East of Baoheng Road, South of Anping County, Hebei P.R China.

Website: <http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613



Specifications

Panel size					Post	
Panel heights	Panel Width	Wire	Mesh Holes	V Beam	Height(mm)	Post Section
630mm	2.0m&2.5m	3-8mm		2	1200	
1030mm	2.0m&2.5m	3-8mm		2	1600	
1230mm	2.0m&2.5m	3-8mm	50×100mm	2	1800	40×60mm
1530mm	2.0m&2.5m	3-8mm	50×150mm	2,3	2100	60×60mm
1730mm	2.0m&2.5m	3-8mm	50×200mm	3	2300	60×80mm
2030mm	2.0m&2.5m	3-8mm		3,4	2600	75×75mm
2230mm	2.0m&2.5m	3-8mm		4	2800	80×80mm
2430mm	2.0m&2.5m	3-8mm		4	3000	

Above are general specification,others are available.

Material

Panel wire:Q195&Q235 Low carbon wire

Post:Q235,345 Steel tube

Panel wire and post material used hot dipped galvanized material, Or black material

Bolts:M8 anti-vandal steel or stainless steel

Surface:Galvanised or galvanised then powder coated&pvc coated finished

Steel grade can be chose.

Powder from AKZONOBEL

Trade Item

Delivery Terms:FOB, CIF

Payment Currency:USD, EUR, AUD,JPY, CAD, GBP, CNY

Payment Item:T/T, L/C, PayPal, Escrow

Nearest Port:Xingang port,Qingdao port

Delivery Time:General after 25days upon received T/T30% advance payment

Popular Payment detail: T/T 30% in advance as deposit, the balance against received the copy of B/L.

Company:Anping County Hangtong Wire Mesh Co.,Ltd.

Address:East of Baoheng Road,South of Anping County,Hebei P.R China.

Website:<http://www.hangtongfence.com> Email: info@hangtongfence.com TEL: 86-318-751633 FAX: 86-318-7529613