

Anping County Hangtong Wire Mesh Co.,LTD Best fence for global market.

Airport Fence



Description

Airports and aviation buildings are sensitive areas that require perimeter fencing solutions that stand up to the high risk levels. There are also demands from a legislative and legal aspects that are often unique to aviation based environments.

Most airport fencing projects will demand a solution that excellent protect the airport area. We used 3D fence panel with concertina razor wire as a general type. It is a type of welded wire mesh which has V-shaped strengthen bending curves. It is made of high quality low carbon steel wire, galvanized wire. Then will be hot dipped galvanized, powder coated or pvc coated. It looks modern and attractive. Mainly used for security protection in construction site, residential building, sports field, warehouse, highway or airport service area, railway station, etc. The height are available in a range of heights from 2500 till 3000 mm. The popular wire diameter is 5.0 mm, mesh holes are 50×100 mm, others are available. The razor wire popular is diameter 500 mm.

Posts are manufactured from steel tubular section with threaded inserts for fixing the steel mesh clips. Additional fixings are provided to accommodate stepping of panels where the fence is installed on a gradient.

The general post section are 60×60 mm, others are available.

Concertina razor wire adopted galvanized material or electrophoresis razor wire(Patent product).

HT-Fence welded wire panel fence is manufactured from galvanised material, powder coated and pvc coated. The popular color is Green RAL 6005 .If others color is required, we're easily able to provide this.All of our fence power from AKZONOBEL Company, paint from Nippon Company.

Airport fence Features

- Attractive and cost effective solution.
- Panels have a high level of rigidity
- Qucik and Easy install
- Various color choice.

Airport fence Application

It is often used in airport, prison, commercial, industry where need perimeter security area, etc.

Specifications



Anping County Hangtong Wire Mesh Co.,LTD Best fence for global market.

Panel size					Post	
Panel heights	Panel Width	Wire	Mesh Holes	V Beam	Height(mm)	Post Section
2000mm	2.5m&3.0m	5.0mm	50×100mm	4	2400	60×60mm
2500mm	2.5m&3.0m	5.0mm		4	3000	

Fence install height Razor wire Diameter

2500mm Φ 500, Φ 600, 3000mm Φ 500, Φ 600,

Above are general specification, others are available.

Materail

Panel wire:Q195&Q235 Low carbon wire

Post:Q235,345 Steel tube

Razor wire:Q235 galvanzied material with 50-60g/m2&200g/m2 zinc coating or electrophoresis coating.

Panel wire and post material used hot dipped galvanized material, Or black materral

Bolts:M8 anti-vandal steel or stainless steel

Surface:Galvanised or galvanised then powder coated&pvc coated fininshed

Steel grade can be chose.

Powder from AKZONOBEL and NIPPON

Trade Item

Delivery Terms:FOB, CIF

Payment Currency: USD, EUR, AUD, JPY, CAD, GBP, CNY

Payment Item:T/T, L/C, PayPal, Escrow

Nearest Port:Xingang port,Qingdao port

Delivery Time: General after 25days upon received T/T30% advance payment

Popular Payment detail: T/T 30% in advance as deposit, the balance against received the copy of B/L.